

PIUSI MA 130 AIR-OPERATED DIAPHRAGM PUMP FOR OIL F00208A00

F00208A00

FLUID COMPATIBILITY

Oil

Premium 50 L/min air-operated diaphragm pump for clean or waste oils, 1/2 BSP ports. Safe for hazardous areas, self-priming to 3 metres dry.



FEATURES

- In/Out Interchangeable
- Long Life Diaphragm
- Built-in Diffuser
- Suitable for Immersed Installations
- Heavy Duty
- Study Design

TECHNICAL SPECIFICATIONS

Flow Rate	50 L/min at typical shop air pressure
Connection	DN15 (1/2 BSP) inlet and outlet
Weight	5.5 kg
Material	NBR
Self	priming - handles dry starts, lifts from drums and sumps

Air	operated - no electric motor, intrinsically safe design
Run	dry safe - won't seize or overheat if the tank empties mid-transfer
Reversible Operation	swap air ports to reverse flow for tank purging
Field Serviceable	diaphragm and valve kits available for rebuild
Diaphragm Seals	NBR construction for petroleum products

USE CASE & APPLICATION

- Workshop waste oil collection
- Diesel transfer in hazardous areas
- Hydraulic oil top-up from drums
- Mobile service truck dispensing
- Field lube service units
- Bulk tank draining and purging