PRODUCT DATA SHEET

PIUSI HOSE REEL SPRING REWIND C/W 25MM ID X 15M F0075026B

F0075026B

FLUID COMPATIBILITY

Diesel

Premium 25mm x 15m spring-rewind diesel hose reel from Piusi. Cast iron construction for heavy-duty workshop or fleet refuelling.

FEATURES

- Automatic spring rewind fuel hose reel
- Sturdy steel structure
- Steel Hub
- Reduced pressure loss through hydraulic sizing

BENEFITS

- Protected latch mechanism which prevents injury
- Adjustable arm brackets for easy positioning
- Optional fixed or rotating support plate

TECHNICAL SPECIFICATIONS

Max Pressure (Bar)	15
Pressure Loss (Bar)	0.8 @ 80 lpm
Length (m)	15
Inlet	1" F BSPP Swivel
Outlet	1" M BSPP

USE CASE & APPLICATION

- Fleet depot diesel dispensing
- Workshop refuelling stations
- Mining site bulk transfer
- Agricultural diesel storage
- Heavy vehicle servicing bays

DIESEL HOSE REEL

FEATURES

- STURDY STRUCTURE
- HAND PROTECTION
- CORROSION RESISTANCE
- REDUCED PRESSURE LOSS
- HEAVY DUTY CONDITIONS

PIUSI automatic DIESEL HOSE REELS for diesel have been designed to ensure high efficiency. The sturdy structure can guarantee the best performance also in heavy duty conditions.

PERFORMANCE

15 BAR	MAX 20 MT
MAX OPERATING PRESSURE	LENGTH HOSE BOUND

AUTOMATIC HOSE REEL WITH HOSE

HOSE DIESEL HOSE REEL FOR 12M HOSE VERSION

PACKAGING

CODE	WEIGHT		PACKAGING			N. BOXES / EUROPALLET	
	KG	LBS	MM	INCH	PCS/BOX	✈	🚢
WITHOUT HOSE							
F0075000A	19	41,9	550X260X540	-	1	12	20
F0075001A	18	39,7	550X260X540	-	1	12	20
F0075008A	15	33,1	550X260X540	-	1	12	20
F0075025A	22,3	49,1	560X350X560	-	1	12	20
F0075018B	21	46	550X260X540	-	1	12	20
WITH HOSE							
F0075002B	26	57,3	550X260X540	-	1	12	20
F0075003B	25	55,1	550X260X540	-	1	12	20
F0075023B	25	55,1	550X260X540	-	1	12	20
F0075004B	22	49,5	550X260X540	-	1	12	20
F0075012B	22	49,5	550X260X540	-	1	12	20
F0075009B	18	39,6	550X260X540	-	1	12	20
F0075010B	27	59,5	550X260X540	-	1	12	20
F0075019B	27	59,5	560X350X560	-	1	8	12
F0075026B	27	59,5	560X350X560	-	1	8	12

ANY BIODIESEL | AIR | ANTIFREEZE | AdBlue® | BIODIESEL | **D** DIESEL | FOOD | GASOLINE | GREASE | KEROSENE | OIL | WATER | WINDSCREEN

INSTALLATION&DIMENSIONS

Different ways to install PIUSI's hose reels: they can be easily placed wherever you need them without any problem about functionality and safety. PIUSI's products are without a doubt designed to support your work in any condition.

IN THE BOX

- REEL
- WALL MOUNT BRACKET
- INSTRUCTION MANUAL

ROOF INSTALLATION



WALL INSTALLATION



GROUND INSTALLATION



MODEL	HOSE REEL XL	HOSE REEL BIG	HOSE REEL SMALL
A	512	495	475
B	470	460	460
C	227	152	102
D	200	200	150
E	322	246	196
F	160	150	150
G	260	200	150
H	12	12	12
L	382	306	256



HOSE REEL FRONT / SIDE



Dimensions expressed in millimeters

DETAILS

4 ROLLS HOSE GUIDE

AUTOMATIC HOSE REELS

DIFFERENT INSTALLATIONS

STURDY DESIGN

MATERIALS

- BODY: CAST IRON
- HUB: SYNTHERED STEEL
- TUBE: RUBBER

TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	HOSE	MAX OPERATING PRESSURE	PRESSURE DROP	INLET	OUTLET	HOSE MAX LENGTH BOUND	HOSE LENGTH
			BSP	BAR	TYPE	WITH SWIVEL BSP	HOSETAIL BSP	METERS	METER
WITHOUT HOSE									
F0075000A	HOSE REEL 3/4" BIG	D	3/4"	10	0,15 @ 60 L/MIN	1" MALE	3/4"	14	-
F0075001A	HOSE REEL 1" BIG	D	1"	10	0,2 @ 80 L/MIN	1" MALE	1"	10	-
F0075008A	HOSE REEL 3/4" SMALL	D	3/4"	10	0,15 @ 60 L/MIN	1" MALE	3/4"	10	-
F0075025A	HOSE REEL 1" XL HEAVY DUTY (STEEL HUB)	D	1"	15	0,5 @ 80 L/MIN	1" FEMALE	1" MALE	15	-
F0075018B	HOSE REEL NAKED XL 15M	D	1"	10	0,2 @ 80 L/MIN	1" FEMALE	1" MALE	15	-
WITH HOSE									
F0075002B	HOSE REEL 8X1" BIG	D	1"	10	0,6 @ 80 L/MIN	1" FEMALE	1" MALE	-	8
F0075003B	HOSE REEL 10X1" BIG	D	1"	10	0,7 @ 80 L/MIN	1" FEMALE	1" MALE	-	10
F0075023B	HOSE REEL 10X1" BIG HEAVY DUTY (STEEL HUB)	D	1"	10	0,7 @ 80 L/MIN	1" FEMALE	1" MALE	-	10
F0075004B	HOSE REEL 10X3/4" BIG	D	3/4"	10	0,7 @ 60 L/MIN	1" FEMALE	1" MALE	-	10
F0075012B	HOSE REEL 10X3/4" BIG	D	3/4"	10	0,7 @ 60 L/MIN	1" FEMALE	3/4" MALE	-	10
F0075009B	HOSE REEL 8X3/4" SMALL	D	3/4"	10	0,6 @ 60 L/MIN	1" FEMALE	1" MALE	-	8
F0075010B	HOSE REEL 14X3/4" BIG	D	3/4"	10	0,6 @ 60 L/MIN	1" FEMALE	1" MALE	-	14
F0075019B	HOSE REEL 15X1" XL	D	1"	15	1 @ 80 L/MIN	1" FEMALE	1" MALE	-	15
F0075026B	HOSE REEL 15X1" XL HEAVY DUTY (STEEL HUB)	D	1"	15	0,8 @ 80 L/MIN	1" FEMALE	1" MALE	-	15

MINIMUM RADIUS OF CURVATURE FOR 3/4 HOSE SIZES "AND 1" OF AT LEAST 130MM; ELECTRICALLY, THE HOSE MUST BE CONDUCTOR R<1 MOhm/m